

PALMAKO PAINTING - GARDEN HOUSES

With our new painting technology, we offer a selection of cabins with exteriors painted in pre-defined color combinations. Each cabin features a main color and an accent color, ensuring a balanced and durable finish. While the exterior is painted, the interior remains untreated, allowing you to customize it with a different color or preserve the natural wooden look with a protective stain finish.

To prevent warping, cupping and moisture damage to both the untreated interior and the treated exterior, it is strongly recommended to also treat the interior of the cabin.



Andrea 11,2+7,9 m² Slide
PNT7042A1

The finishing of garden house components is carried out using a spray method, which is an effective and widely applied technique for the high-quality finishing of various products. To ensure better adhesion and finishing quality, the surface to be painted is roughened prior to painting. During the painting process, the house components moving on a conveyor are automatically coated with an even layer of spray paint. The painted components are then directed to a dedicated drying chamber.

After the painting and drying stages, all components are packaged in weather-resistant packaging. The layers are separated by a thin plastic film. The house kit includes touch-up paint: 0,5 L paint of main color and 0,5 L paint of accent color (if selected).

SIKKENS RUBBOL FACADE SPECIAL

For our factory-painted garden houses, we use Sikkens Rubbol Facade Special – a high-quality, water-based paint made for wooden surfaces. It offers excellent weather protection, UV resistance, and long-lasting color, keeping your garden house looking great for years.



Art. No.	Description
	PNT7042A* light grey + anthracite (RAL7042 + RAL7016)
	PNT7012A* dark grey + anthracite (RAL7012 + RAL7016)
	PNT9016A* white + anthracite (RAL9016 + RAL7016)
	PNT7042W* light grey + white (RAL7042 + RAL9016)
	PNT7012W* dark grey + white (RAL7012 + RAL9016)
	PNT9016W* white + white (RAL9016 + RAL9016)
	PNT7042H* light grey + light grey (RAL7042 + RAL7042)
	PNT7012G* dark grey + dark grey (RAL7012 + RAL7012)

COLORS

Depending on the product, each cabin offers a selection of specific color combinations to choose from. The specified gloss level is 25-35 but may vary due to factors such as surface absorbency, coat thickness, application method, and other conditions. The main color is shown on the left, with the accent color on the right.

*The asterisk is a placeholder for a modification number of a paint recipe specifying which parts of the product are painted.

Bringing joy to the garden

Palmako
LEMEKS GROUP

THE DESCRIPTION OF PAINTING THE CABINS

	Modern corner connection cabins, Element houses	Chalet-cut log cabins	Canopy roofs	Post and beam construction, windows and doors
Wall logs/ Elements	Painted outside	Painted outside		
Log ends		Painted all sides		
Doors and windows	Painted all sides	Painted all sides		
External slats	Painted all sides	Painted all sides	Painted all sides	
Floor boards	Natural	Natural	Natural	
Roof boards	Natural	Natural	Natural	
Rafters, purlins	Natural	Natural	Natural	
Internal details	Natural	Natural		
Foundation beams	Brown dipped	Brown dipped		Brown dipped
Rear wall			Painted all sides	
Posts			Painted all sides	
Front and back rafter			Painted all sides	
Louvre wall			Painted all sides	
Middle rafters			Natural	
All wooden details				Painted all sides



PNT7042A2



PNT7012A1



PNT7042A1



PNT7042W1



PNT7012A2



PNT9016W5



PNT9016W2



PNT7012G5



PNT7012G6



PNT7042H6

Important! As the wall logs are finished on only one side, the cabin must be installed as shown and cannot be reversed. Please follow the instructions carefully to ensure the best fit.

COLOR TONE ACCURACY

The actual color tone may differ from what is displayed in product catalogs and other electronic presentations due to the printing technology and screen displays.

INSTRUCTIONS FOR HANDLING PAINTED COMPONENTS

- To avoid mechanical damage and damage to the paint layer, the packaging and components must be handled carefully.
- Components should always be placed on a soft and non-abrasive surface.

MAINTENANCE

- Check the condition of the paint coating every six months.
- At least once every two years, clean the painted wooden surface with soapy water or a neutral cleaner to remove dirt and mold.
- For minor damages, such as paint peeling, resin exudation, or color changes, perform touch-ups. To avoid color differences, it may be necessary to repaint the entire product.
- If the paint peels due to volume changes in the wood, cracking, or resin exudation, the following actions must be taken:
 - Clean the surface until it reaches clean wood using a scraper or nylon brush.
 - Remove dust and prime the surface with a biocidal impregnation primer.
 - Apply the finish in 1–2 coats as needed, following the paint manufacturer's instructions.

VENTILATION

In a finished house, it is important to ensure continuous air exchange. In a room without proper ventilation, excess moisture can accumulate, which may damage the wood and paint coating. The simplest and most effective solution to prevent excess moisture is the addition of ventilation grilles.



Wall logs painted outside, natural inside



Painted wall logs